



LOW PRESSURE STEEL CYLINDER SPECIFICATIONS

Cylinder	DOT Specification	LPG Capacity gal (liters)	Cylinder Volume cu. in (liters)	Outside Diameter in (mm)	Overall Length in (mm)	Empty Weight lbs (kg)	Water Capacity lbs (kg)
1 L	DOT 4B240ET	.24 (.9)	55 (0.901)	3 (76.2)	9.38 (238.1)	2 (0.91)	2 (0.91)
LP 2.5	DOT -4BW240	2.5 (9.4)	726 (11.8)	9.125 (231.8)	16.625 (422.3)	13.5 (6.1)	26.2 (11.8)
LP 5	DOT -4BW240	4.7 (17.8)	1318 (22)	12.125 (308)	17.625 (447.6)	17.7 (8.0)	47.7 (21.6)
LP 143	DOT-4BW260	114.4 (51.88)	3958 (64.87)	11.89 (302)	40 (1016)	48 (21.77)	143 (64.86)
LP 239	DOT -4BW240	22.9 (86.7)	6596 (108.1)	14.625 (371.5)	48.5 (1232)	72.0 (32.6)	240 (108.1)

DCG PARTNERSHIP COMPRESSED GAS STEEL CYLINDERS ARE CONSTRUCTED IN ACCORDANCE WITH CFR 49 PART 178.61. CYLINDERS COMPLY WITH U.S. DEPARTMENT OF TRANSPORTATION SPECIFICATIONS. EVERY CYLINDER IS THOROUGHLY INSPECTED AND TESTED BY AN INDEPENDENT INSPECTION AGENCY APPROVED BY THE DEPARTMENT OF TRANSPORTATION.

