
Standard Test Method for Kinematic Viscosity of Transparent and Opaque Liquids (and the Calculation of Dynamic Viscosity) in Accordance with ASTM D 445

DCG has available Viscosity Reference Standards for the determination of the kinematic viscosity of liquid petroleum products, both transparent and opaque, in compliance with ASTM D 445. The certified viscosity values have been determined in accordance with ASTM 445 and are packaged in 500 mL amber glass bottles.

Part #: DCGVIS110

Description: 110 cSt viscosity @ 40° C

Part #: DCGVIS60

Description: 54 cSt viscosity @ 40° C

Part #: DCGVIS10

Description: 9.5 cSt viscosity @ 40° C

Part #: DCGVIS130

Description: 130 cSt viscosity @ 40° C

Part #: DCGVIS100

Description: 102 cSt viscosity @ 40° C

Part #: DCGVIS30

Description: 30 cSt viscosity @ 40° C

Part #: DCGVIS300

Description: 300 cSt viscosity @ 40° C

Part #: DCGVIS520

Description: 520 cSt viscosity @ 40° C

Part #: DCGVIS920

Description: 920 cSt viscosity @ 40° C



4170 A Main Pearland, TX 77581 PH: 281-648-1894 FAX: 281-648-1895
www.dcgpartnership.com
E-mail: customerservice@dcgpartnership.com

Chromatographic Reference Materials