

## **Standard Test Method for Distillation of Petroleum Products at Atmospheric Pressure in Accordance with ASTM D 86 For Groups 1, 2 and 4**

DCG has available calibration standards to be used in accordance with ASTM D 86 Group 1, 2 and 4 products. Group 1 and 2 standards are a synthetic blend of hydrocarbons that boil in the temperature range specified in ASTM D 86. This calibration standard covers a boiling range of 129 to 368° F (54 to 187° F) and was verified by consensus analysis. The calibration standard for Group 4 is diesel oil characterized with a distillation range from 410 to 670° F (210 to 355° C) and has also been verified by consensus analysis.

### **ASTM D 86 Groups 1 & 2 Synthetic Distillation Calibration Standard**

#### **Part #: DCGD86-1**

Description: Synthetic distillation standard containing 0.5L

#### **Part #: DCGD86-2**

Description: Synthetic distillation standard containing 2 x 0.5L

#### **Part #: DCGD86-3**

Description: Synthetic distillation standard containing 4 x 0.5L

### **ASTM D 86 Group 4 Distillation Calibration Standard**

#### **Part #: DCGD-4-1**

Quantity: 0.25L

#### **Part #: DCGD-4-2**

Quantity: 0.5L



4170 A Main Pearland, TX 77581 PH: 281-648-1894 FAX: 281-648-1895  
www.dcgpartnership.com  
E-mail: customerservice@dcgpartnership.com

**Chromatographic Reference Materials**